


## DIN 6798


### Serrated lock washers



type A = external teeth



type I = internal teeth



type V = countersunk

\* acc. to DIN 6798:1971

Dimensions	2.2	2.5*	2.7	3.2	3.7	4.3	5.3
$d_{2 \text{ form A/I}}$	4.5	5	5.5	6	7	8	10
$d_{2 \text{ type V}}$	-	-	-	6	7	8	9.8
$S_{\text{type A/I}}$	0.3	0.4	0.4	0.4	0.5	0.5	0.6
$S_{\text{type V}}$	-	-	-	0.2	0.25	0.25	0.3
for thread $\varnothing$	2	2.3	2.5	3	3.5	4	5

Dimensions	6.4	7.4	8.4	10.5	13	15	17
$d_{2 \text{ form A/I}}$	11	12.5	15	18	20.5	24	26
$d_{2 \text{ type V}}$	11.8	-	15.3	19	23	-	-
$S_{\text{type A/I}}$	0.7	0.8	0.8	0.9	1	1	1.2
$S_{\text{type V}}$	0.4	-	0.4	0.5	0.5	-	-
for thread $\varnothing$	6	7	8	10	12	14	16

Dimensions	19	21	23	25	28	31
$d_{2 \text{ form A/I}}$	30	33	36	38	44	48
$d_{2 \text{ type V}}$	-	-	-	-	-	-
$S_{\text{type A/I}}$	1.4	1.4	1.5	1.5	1.6	1.6
$S_{\text{type V}}$	-	-	-	-	-	-
for thread $\varnothing$	18	20	22	24	27	30

### Dimensions in stock:

Steel/Steel coated: 294 | Stainless steel: 519 | Non-ferrous materials: 591